



Y S I Environmental

## YSI 550A Dissolved Oxygen Instrument


### *Loaded with improved functionality*

Looking for a rugged, field-worthy instrument for measuring dissolved oxygen? The new YSI 550A DO instrument features a waterproof (IP-67), impact-resistant case and innovative field-replaceable DO electrode modules. Measure dissolved oxygen and temperature simultaneously using YSI's proven polarographic technology for oxygen and YSI Temperature Precision™ thermistors, the planetwide standard for accuracy. Our new PE membranes provide faster response times with less stirring dependence - saving time with every reading!



- Faster response time!
- Waterproof! Meets IP-67 specifications
- Field-replaceable DO electrode modules
- Screw-on cap membranes
- PE membranes lessen stirring dependence!
- Over 2000 hours battery life
- Calibrate in either mg/L or % saturation

- User-selectable temperature units (°C or °F)
- 12, 25, 50 and 100-foot cable lengths
- Manual salinity input from 0 to 70 ppt
- **Three-year** instrument warranty, one-year on the DO module!



Pure  
Data for a  
Healthy  
Planet.®

*Longest battery  
life in the industry!*

### **Packed with features**

Measurements are fast and easy with one-hand operation, an easy-to-use backlit display, low-battery indicator, automatic push-button calibration, and a weighted, quick-sinking probe. The YSI 550A DO has a built-in calibration chamber, direct salinity, temperature, and altitude compensation. The instrument provides simultaneous readings of oxygen and temperature. **DO readings include our expanded range of 0-50 mg/L!**

[www.YSI.com](http://www.YSI.com)



To order, or for more  
information, contact  
YSI Environmental.

+1 937 767 7241  
800 897 4151 (US)  
www.ysi.com

YSI Environmental  
+1 937 767 7241  
Fax +1 937 767 9353  
environmental@ysi.com

Endeco/YSI  
+1 508 748 0366  
Fax +1 508 748 2543  
systems@ysi.com

SonTek/YSI  
+1 858 546 8327  
Fax +1 858 546 8150  
inquiry@sontek.com

YSI Environmental Gulf Coast  
+1 225 753 2650  
Fax +1 225 753 8669  
environmental@ysi.com

YSI Hydrodata (UK)  
+44 1462 673 581  
Fax +44 1462 673 582  
europe@ysi.com

YSI Middle East (Bahrain)  
+973 1753 6222  
Fax +973 1753 6333  
halsalem@ysi.com

YSI (Hong Kong) Limited  
+852 2891 8154  
Fax +852 2834 0034  
hongkong@ysi.com

YSI (Qingdao) Limited  
+86 532 575 3636  
Fax +86 532 571 0101  
ysiqd@ysiqd.com.cn

YSI Nanotech (Japan)  
+81 44 222 0009  
Fax +81 44 221 1102  
nanotech@ysi.com

**ISO 9001**  
**ISO 14001**

Who's Minding the Planet? and Pure  
Data for a Healthy Planet are trade-  
marks of YSI Incorporated.

©2007 YSI Incorporated  
Printed in USA 0107 W52-04

CE

*YSI incorporated*  
Who's Minding  
the Planet?™

**Y S I Environmental**

## 550A System Specifications (Instrument, Sensor, Cable)

	Range	Resolution	Accuracy
Dissolved Oxygen % Saturation	0 to 500%	0.1% air saturation or 1%; selectable	0 to 200%: ±2% of reading or 2% air saturation, whichever is greater; 200 to 500%: ±6% of reading
Dissolved Oxygen mg/L	0 to 50 mg/L	0.01 mg/L or 0.1 mg/L; selectable	0 to 20 mg/L: ± 0.3 mg/L or 2% of reading, whichever is greater; 20 to 50 mg/L: ±6% of reading
Temperature (°C or °F)	-5 to +45°C	0.1°C	±0.3°C

Medium	Fresh, sea, or polluted water
Dissolved Oxygen Sensor	Steady-state polarographic
Dissolved Oxygen Probe	Field-replaceable module
Parameter Compensation	Automatic temperature compensation for dissolved oxygen Automatic salinity compensation (0-70 ppt) for dissolved oxygen Altitude compensation for calibration
Size	4.7 in. width; 9 in. length (11.9 cm x 22.9 cm)
Weight with batteries	2 lb. (0.91 kg)
Power	4 alkaline C cells
Battery Life	Over 2000 hours at 25°C
Cables	12, 25, 50, or 100- foot lengths
Other Features	Waterproof to IP-67 High-impact resistance Push-button calibration Built-in calibration chamber Large, backlit display Low battery indicator on display Manual salinity input CE compliance
Warranty	3-year for the instrument 1-year for the DO module

## 550A Ordering Information

550A-12, 25, 50 or 100	Instrument with 12, 25, 50 or 100-foot cable and probe
550A-12CC, 25CC, 50CC, or 100CC	Instrument with 12, 25, 50 or 100-foot cable and probe with carrying case
5908	Membrane kit, 1.25 mil PE (6 caps and bottle of KCl)
559	User-replaceable DO electrode
5085	Hands-free harness
5065	Form-fitted case with shoulder strap
5060	Soft-sided carrying case with storage



**TTT Environmental**  
Instruments and Supplies

*The preferred source for instrument  
Rentals, Sales, Service and Supplies!*

4201 B Street  
Anchorage, AK 99503  
(907) 770-9041

www.tttenviro.com

25420 74<sup>th</sup> Avenue S.  
Kent, WA 98032  
(253) 373-9041

info@tttenviro.com