



GA-92XTd Specifications:

*The preferred source for instrument
Rentals, Sales, Service and Supplies!*

4201 B Street
Anchorage, AK 99503
(907) 770-9041

25420 74th Avenue S.
Kent, WA 98032
(253) 373-9041

www.tttenviro.com

info@tttenviro.com



XTd Model

with LCD gain, battery and signal strength/polarity display

Audio Output	Audio Signal increases in frequency with gradient-field intensity. Idle frequency = 10 Hz
Visual Output	Expanding bar graphs indicate polarity (+ or -) and relative strength (GA-92XTd model only)
Battery Life	24 Hours (intermittent usage)
Input Power	Supplied by one 9-volt lithium battery
Battery Indicator	4-segment LCD
Volume	Continuous control
Gain	Continuous control, with range indicated by a 4-segment LCD at each quarter turn, L @ 0-1/4, M @ 1/4-1/2, H @ 1/2-3/4, XH 3/4-Full
Weight	Approximately 2.4 lb. (1.1 kg)
Operating Temp	-13° F to 140° F (25° C to 60° C)
Overall Length	Unit extended: 26 in. (~66 cm) Unit collapsed: 15.5 in (~39 cm)
Water Resistant Length	11.5 in. (~29 cm) (when extended)
Nominal Sensor Spacing	9.5 in. (~24 cm)
Construction	30% glass-filled nylon, high impact ABS, .2" (~5 mm) wall thickness