



Radiodetection
Dielectric Technologies
AN SPX BRAND



TTT Environmental
Instruments and Supplies

*The preferred source for instrument
Rentals, Sales, Service and Supplies!*

4201 B Street
Anchorage, AK 99503
(907) 770-9041

www.tttenviro.com

25420 74th Avenue S.
Kent, WA 98032
(253) 373-9041

info@tttenviro.com

Model MGD-2002

Multi-Gas Leak Locator

Leak detection made easy is the premise behind the Radiodetection/Dielectric MGD-2002 Multi-gas Detector. Through the use of a common tracer gas such as Helium or Hydrogen, leaks in most pressurized systems can be located with pinpoint accuracy.

Proven successes have been demonstrated for many disciplines such as Telecom's, Municipalities, Building Contractors, Plumbers, HVAC Technicians, Tank Inspectors and many more.

Whether you're identifying leaks in underground tanks, pipes, cables or tracing a leak in almost any pressurized system. The MGD-2002 has the sensitivity you'll need to accurately and efficiently locate the leak. The MGD-2002 performs equally well with either Helium or Hydrogen* used as a tracer gas.



Helium is non-polluting, non-reacting and safe to use, making it the ideal tracer gas when applied to critical systems. In addition, the sensitivity of the MGD allows Helium to be mixed with ambient air in large volume systems further reducing the cost of use.

Convenient and easy to use, the MGD-2002 is designed for one-handed operation of all functions. Equipped with a tactile membrane keypad, all selections are easily confirmed with a distinctive "click" and the backlit display can be viewed in all light conditions. The MGD-2002 is supplied with a built-in headphone jack for use with the audio indicator.

The MGD-2002 is equipped with a rechargeable Ni-MH battery pack that provides over 8 hours of use per charge. Operating life can be further extended with an additional battery, available as an accessory, that can be installed in seconds. In addition, the Multi-Gas Detector can be recharged with the AC or car adaptors included in the kit.

With only a 30 second Power-On Self Test the Multi-Gas Detector is ready to go when you are!

154 Portland Road, Bridgton, Maine 04009

Phone: (207) 647-9495 Toll Free: 1-877-247-3797 Fax: (207) 647-9496 Email: rd.sales.us@spx.com

Model MGD-2002

Multi-Gas Leak Locator

Highlights

- Pinpoint accuracy with sensitivity from 25 PPM up to 100% concentration
- Operates in automatic (survey) mode or manual mode
- Utilizes either Helium or Hydrogen* as a tracer gas
- Field replaceable moisture removing cartridge in wand
- Lightweight, telescoping ground probe with boot
- Rapid charging Ni-MH battery with AC and car adaptors

Leak Locating Applications

Industrial:

- Industrial Air/Gas/Liquid Piping Systems
- Welds, Joints, Seams, Gaskets
- Aircraft Oxygen Systems
- Electronics Chip Doping
- Medical Device Testing
- Refrigeration System

Contractors:

- Under Slab or Buried Piping Systems
- Secondary Containment Systems
- Buried Water Services
- Radiant Heat Flooring

Telecom:

- Direct Buried Telephone Cables
- Underground Ducted Cables
- Air Pipe Systems
- Splice Cases

Municipalities:

- Municipal Water Systems

Features

- Tactile Membrane Keypad
- Backlit LCD Display
- Moisture Indicator in Wand
- Field Replaceable Battery
- Headphone Jack for Audible Monitoring
- Time-lapse Bar Graph Display
- Serial Port Output (optional)

Ordering Information

| Part No. | Description |
|----------|---|
| 83219 | MGD-2002 Multi-Gas Detector Complete Leak Locating Kit with Case |
| 83220 | Replacement Moisture Trap Cartridge |
| 82492 | Spare Battery |
| 882-0007 | Headphones (Not Contained in Kit) |

Warranty

Radiodetection warrants that this product shall be free from defects in workmanship and materials for one year. For details please see our warranty statement.

* Dielectric recommends Helium as a tracer gas since the molecular size of Helium is not significantly larger than that of the diatomic Hydrogen molecule and Helium does not react with any other substances. However, if Hydrogen is to be used as the tracer gas a ready-made Hydrogen dilution that is well below the OSHA approved LEL (flammability) limit MUST be used.

Specialists in Leak Locating