

Soaring To New HEIGHTS

The Legacy Continues



Refineries



Fire & Hazmat



Landfills





Natural Gas



EAGLE 2




Specifications


Enclosure	Weatherproof, chemical resistant, anti RFI / EMI coated high impact polycarbonate - PBT blend. Can operate in rain or be set into 2.0" of water without leakage. Ergonomically balanced with rugged top mounted handle.
Dimensions	9.5" L x 5.25" W x 5.875" H (241mm L x 140mm W x 149mm H)
Weight	3.8 Lbs (1.72kg) (standard 4 gas with batteries)
Detection Principle	Catalytic combustion, electrochemical, galvanic, infrared, photo ionization, and thermal conductivity.
Sensor Life	2 Years under normal conditions.
Sampling Method	Powerful, long-life pump (over 6,000 hours) can draw samples over 125 feet. Flow rate approximately 2.0 SCFH
Display	Backlit 128 x 64 graphics display. Viewed through window in case top. Displays readings & status of all 6 channels simultaneously. Backlight, illuminates for alarms and on demand with adjustable time. Optional mode allows automatic or manual scrolling display of just one gas at a time with very large characters.
Language	Readout can display in 5 languages (English, French, German, Italian, or Spanish).
Alarms	2 Alarms per channel plus TWA and STEL alarms for toxics. The two alarms are fully adjustable for levels, latching or self reset, and silenceable.
Alarm Method	Buzzer 95 dB at 30 cm, four high intensity LED's.
Controls	4 External glove friendly push buttons for operation, demand zero, and autocalibration. Buttons also access LEL/ppm, % Vol. alarm silence, peak hold, TWA/STEL values, battery status, conversion factors, and many other features.
Continuous Operation	At 70°F, (21°C) 16 hours using alkaline batteries, or 18 hours using Ni-MH.
Power Source	4 Alkaline or Ni-MH, size C batteries (Charger has alkaline recognition to prevent battery damage if charging is attempted with alkalines).
Operating Temp. & Humidity	-4°F to 122°F (-20°C to 50°C) 0 to 95% RH, non-condensing.
Response Time	30 Seconds to 90% of range (for most gases) using standard 5 ft hose.
Safety Rating	Intrinsically Safe, Class I, Division 1, Groups A, B, C, D.
	Approvals:  
Standard Accessories	Shoulder strap, alkaline batteries, hydrophobic probe, 5 foot hose, and internal hydrophobic filter
Optional Accessories	<ul style="list-style-type: none"> • Dilution fitting (50/50) • Ni-MH batteries • Battery charger, 115 VAC, 220 VAC, or 12 VDC (charge time 4 hours)/ continuous operation adapter, 115 VAC or 12 VDC • Extension hoses
Warranty	Two year material and workmanship, one year for PID sensor


Specifications subject to change without notice

Sensor Technologies


Standard 4 Gas


Catalytic		
		
Gas	Range	Accuracy
Hydrocarbons (CH ₄ , standard)	0 - 100% LEL	± 5% of reading or ± 2% of full scale (*)
	0 - 5% Vol. (CH ₄)	
	0 - 50,000 ppm (CH ₄)	± 50 ppm or ± 10% of reading (*)
Combustible level detection displayed in % LEL, PPM, or % volume. Methane is the standard configuration. Other combustible gases available.		


Galvanic		
		
Gas	Range	Accuracy
Oxygen (O ₂)	0 - 40% Vol. 0 - 100% Vol.	± 0.5% O ₂
A specific electrochemical sensor for oxygen monitoring.		

Standard Electrochemical		
		
Gas	Range	Accuracy
Carbon Monoxide (CO)	0 - 500 ppm	± 5% of reading ± 2 ppm (*)
Hydrogen Sulfide (H ₂ S)	0 - 100 ppm	
Extra long-life CO and H ₂ S sensors.		


Specialty Sensors

Photo ionization Detection (PID)	
	
Gas	Range
Volatile Organic Compound (VOC)	0 - 50 ppm 0 - 2,000 ppm
Monitor low ppm VOC gases.	

Infrared		
		
Gas	Range	Accuracy
Carbon Dioxide (CO ₂)	0 - 10,000 ppm 0 - 5% Vol. 0 - 60% Vol.	± 5% of reading or ± 2% of full scale (*)
Methane (CH ₄)	0 - 100% LEL 0 - 100% Vol.	
Hydrocarbons	0 - 100% LEL 0 - 30% Vol.	
Monitor combustible gases in inert environments. Monitor wide range of CO ₂ .		

Thermal Conductivity		
		
Gas	Range	Accuracy
Methane (CH ₄)	0 - 100% Vol.	± 5% of reading or ± 2% of full scale (*)
Hydrogen (H ₂)	0 - 10% Vol. 0 - 100% Vol.	
Monitor % volume methane or hydrogen.		

Smart Toxic Sensors

Smart Electrochemical		
		
Gas	Range	Accuracy
Ammonia (NH ₃)	0 - 75 ppm	± 10% of reading or ± 5% of full scale (*)
Arsine (AsH ₃)	0 - 1.5 ppm	
Chlorine (Cl ₂)	0 - 3 ppm	
Hydrogen Cyanide (HCN)	0 - 15 ppm	
Phosphine (PH ₃)	0 - 1 ppm	
Sulfur Dioxide (SO ₂)	0 - 6 ppm	
Monitor a wide variety of toxic gases. Smart plug and play sensors are auto recognized and can be remotely calibrated.		

Note: (*) = Whichever is greater



CONFINED SPACE ENTRY

- Monitor LEL, O₂, CO, and H₂S
- Internal sample pump
 - ◊ *Pull samples up to 125'*
 - ◊ *Maintain steady sample flow to sensors*
- Audible and visual alarms
 - ◊ *2 Ways to communicate with workers*
- Ideal for refinery applications

LEAK INVESTIGATION

- Provides ppm detection of combustible gas
- Barhole mode for tracking leak migration
- Leak check with changing blink / pulsing rate
 - ◊ *LED's and alarm tones increase in frequency as gas concentration increases*
- Audible alarm silence
 - ◊ *Perform leak investigations without alarming residents*



LINE PURGE TESTING

- Thermal conductivity sensor
 - ◊ *0 to 100% volume Methane / Hydrogen range*
- Autoranging IR
 - ◊ *Automatically changes from % LEL to % Vol.*
 - ◊ *Displays appropriate unit of measure*

VOC MONITORING

- Robust photo ionization detector (PID)
- Two ranges available,
 - ◊ *0-50 ppm or 0-2,000 ppm*
- Can be combined with other sensors to maximize capability
- Method 21 compliant



TRANSFORMER TESTING

- Determine transformer health by sampling head space
- Measure Hydrogen (and other flammable gases) and Oxygen in nitrogen blanket
- Increasing flammable gas levels in head space indicates failing transformer



LANDFILL MONITORING

- LEL / PPM and 0-100% volume Methane
- 0-60% Carbon Dioxide range
- Can be combined with other sensors (O₂/H₂S/CO) to maximize capability



Accessories

- A. Calibration station
- B. Battery charger / continuous operation adapter, AC and DC versions
- C. Variety of sample hose lengths
- D. Float probe, auto shut off when probe contacts water
- E. PID service kits
- F. Calibration kits
- G. Carrying cases
- H. Rechargeable Ni-MH batteries



User Selectable Options

Date and Time
 Date Format
 Battery Type
 Configuring Channels
 Combustible Gas Selection
 Catalytic Detection Units
 Relative Response On or Off
 Alarm Points
 Alarm Latching
 Alarm Silence
 User and Station ID
 Autocal Values
 Backlight Delay
 Auto Fresh Air
 Data Log Interval

Data Log Overwrite
 Data Log Memory
 LCD Contrast
 Calibration Reminder
 Calibration Past Due Action
 Calibration Interval
 Leak Check / Bar Hole Mode
 Bar Hole Measurement Time
 Operation Confirmation Alert
 Password Function On or Off
 Factory Default
 Lunch Break
 Language
 Span Factor



Made in USA



10000363



ISO 9001

Toll Free: (800) 754-5165 • Phone: (510) 441-5656 • Fax: (510) 441-5650
www.rkieagle2.com

World Leader In Gas Detection & Sensor Technology



TTT Environmental
 Instruments and Supplies

*The preferred source for instrument
 Rentals, Sales, Service and Supplies!*

4201 B Street
 Anchorage, AK 99503
 (907) 770-9041

www.tttenviro.com

25420 74th Avenue S.
 Kent, WA 98032
 (253) 373-9041

info@tttenviro.com