TTT Environmental
Instruments and Supplies

The preferred source for instrument Rentals, Sales, Service and Supplies!

4201 B Street
Anchorage, AK 99503
(907) 770-9041

25420 74th Avenue S.
Kent, WA 98032
(253) 373-9041

www.tttenviro.com
info@tttenviro.com

En Novative Technologies, Inc.

Terra Core® Sampler

The Cost Effective, Time Saving, Disposable Transfer Tool

- Uniquely designed to be the easiest and most rugged sampler on the market.
- Built-in handle allows samples to be easily taken from hard packed soils.
- Eliminates the need for a field balance.
- No additional handles or tools needed.
- Available in a 5 gram or 10 gram sample size.

Available Online At
www.ennovativetech.com

En Novative Technologies, Inc.
1795 Industrial Drive • Green Bay, WI 54302
Phone: 920-465-3960 • Fax: 920-465-3963
Toll Free: 888-411-0757

En Novative Technologies, Inc.

Recommended Use Of The Terra Core®

NOTE: The Terra Core® Sampler is a single use device. It cannot be cleaned and/or reused.

Step 1

Have ready a 40ml glass VOA vial containing the appropriate preservative. With the plunger seated in the handle, push the Terra Core® into freshly exposed soil until the sample chamber is filled. A filled chamber will deliver approximately 5 or 10 grams of soil.

Step 2

Wipe all soil or debris from the outside of the Terra Core® sampler. The soil plug should be flush with the mouth of the sampler. Remove any excess soil that extends beyond the mouth of the sampler.

Step 3

Rotate the plunger that was seated in the handle top 90° until it is aligned with the slots in the body. Place the mouth of the sampler into the 40ml VOA vial containing the appropriate preservative and extrude the sample by pushing the plunger down. Quickly place the lid back on the 40ml VOA vial. **Note:** When capping the 40ml VOA vial, be sure to remove any soil or debris from the top and/or threads of the vial.

En Novative Technologies, Inc. • 1795 Industrial Drive • Green Bay, WI 54302 • www.ennovativetech.com
Phone: 920-465-3960 • Toll Free: 888-411-0757 • Fax: 920-465-3963