

Levellogger Junior Edge

Model 3001

The Levellogger Junior Edge provides an inexpensive alternative for measuring groundwater and surface water levels and temperature. The Levellogger Junior Edge combines a pressure sensor, temperature detector, a datalogger, and 5-year battery (based on a 1-minute sampling rate) in one compact 7/8" x 5.6" (22 mm x 142 mm) stainless steel housing.

The Levellogger Junior Edge records absolute pressure using the same durable Hastelloy® pressure sensor as the Levellogger Edge. The Hastelloy sensor has excellent performance in harsh environments with better temperature compensation and thermal response time, and can withstand 2 times overpressure without permanent damage.

The Levellogger Junior Edge features FRAM memory, with a capacity of 40,000 sets of temperature and water level data points. Readings are linear at a user-defined interval between 0.5 second to 99 hours. Accuracy is 0.1% FS, with lifetime factory calibration.

If greater accuracy, more sampling options, or wider depth ranges are required, the Solinst Levellogger Edge has the functionality to suit your application (see Model 3001 Edge data sheet). For conductivity datalogging, Solinst also offers the LTC Levellogger Junior (see Model 3001 LTC Levellogger Junior data sheet).

Technical Specifications

Level Sensor:	Piezoresistive Silicon with Hastelloy Sensor
Ranges:	F15/M5, F30/M10
Accuracy:	± 0.1% FS
Units of Measure:	cm, m, ft, psi, kPa, bar, °C, °F
Normalization:	Automatic Temp Compensation
Temp Compensation Range:	0°C to 40°C
Temperature Sensor:	Platinum Resistance Temperature Detector (RTD)
Accuracy:	± 0.1°C
Resolution:	0.1°C
Battery Life:	5 Years (based on 1 reading/minute)
Operating Temperature:	- 20°C to 80°C
Clock Accuracy:	± 1 minute/year (- 20°C to 80°C)
Memory:	FRAM
Maximum Readings:	40,000 sets of readings
Communication:	Optical Infrared to USB, RS232, or SDI-12
Size:	7/8" x 5.6" (22 mm x 142 mm)
Weight:	4.2 oz. (119 grams)
Wetted Materials:	316 Stainless Steel, Delrin®, Viton®, Hastelloy
Sampling Mode:	Linear, Real Time View, Future Start
Measurement Rates:	0.5 sec to 99 hours
Barometric Compensation:	Data Wizard and Barologger Edge



TTT Environmental
Instruments and Supplies

*The preferred source for instrument
Rentals, Sales, Service and Supplies!*

Features

- Low cost
- Accuracy of 0.1% FS
- Memory for 40,000 data points
- Robust Hastelloy pressure sensor
- Basic and advanced data compensation options

4201 B Street
Anchorage, AK 99503
(907) 770-9041

www.tttenviro.com

25420 74th Avenue S.
Kent, WA 98032
(253) 373-9041

info@tttenviro.com

Operation

Programming the Levellogger Junior Edge is the same as with the Levellogger Edge. An Optical Reader or PC Interface Cable connects the Levellogger to a laptop or desktop PC. The intuitive Levellogger Software automatically detects the type of Levellogger that is connected. Programming, downloading, data management and export are intuitive tasks. The Real Time View option allows immediate viewing of live water level and temperature readings, independent of the scheduled programming intervals.

The Levellogger Junior Edge outputs temperature and temperature compensated water level readings. Using the Data Wizard in the Levellogger Software, you can barometrically compensate multiple Levellogger Junior Edge files simultaneously, with just one Barologger Edge file.

The Levellogger Junior Edge is compatible with Levellogger Series accessories, including the Solinst Levellogger App and Interface, the Leveloader Gold data transfer device, SDI-12 Interface Cable, and Solinst Telemetry Systems.

These compact dataloggers are straightforward to deploy. Installation can be with direct read cables, by stainless steel wireline or Kevlar® cord suspension, with the option of using Solinst 2" Locking Well Caps.

Applications



- Monitoring water levels in wells and surface water
- Pump and slug tests
- Reservoir and stormwater runoff management
- Watershed and drainage basin monitoring
- Stream gauging, lake and wetland monitoring
- Tank level measurement



Levellogger App & Interface

A smart alternative to the Levellogger Gold, is the Levellogger App Interface that uses Bluetooth® wireless technology to connect all Levellogger Series products to your Apple® smart device using the Solinst Levellogger App (see Model 3001 Solinst Levellogger App & Interface data sheet).



Model 3001					
		Levellogger Edge	CE WEEE	Levellogger Junior Edge	CE WEEE
Warranty		3 Years		1 Year	
Pressure Transducer		Piezoresistive Silicon with Hastelloy Sensor		Piezoresistive Silicon with Hastelloy Sensor	
Calibrated Ranges:		6, 15, 30, 65, 100, 300, 600 ft, Atm. Barologger 2, 5, 10, 20, 30, 100, 200 m, Atm. Barologger		15, 30 ft 5, 10 m	
Accuracy		± 0.05% FS (Barologger Edge ±0.05 kPa)		± 0.1% FS	
Normalization		Automatic Temperature Compensation		Automatic Temperature Compensation	
Calibration		Factory – Lifetime calibration		Factory – Lifetime calibration	
Response Time (90% Thermal Δ)		1 minute/10°C change		1 minute/1°C change	
Temp Comp Range		0 to +50°C (Barologger Edge -10 to +50°C)		0 to +40°C	
Over-pressure Range		2 X		2 X	
Temperature Sensor		Platinum Resistance Temperature Detector (RTD)		Platinum Resistance Temperature Detector (RTD)	
Temperature Accuracy		± 0.05°C		± 0.1°C	
Temperature Resolution		0.003°C		0.1°C	
Operating Temp Range		-20 to +80°C		-20 to +80°C	
Clock Accuracy		± 1 minute / year (-20°C - +80°C)		± 1 minute / year (-20°C - +80°C)	
Battery Life		10 Years (based on 1 reading/minute)		5 Years (based on 1 reading/minute)	
Size		7/8" x 6.25" (22 mm x 159 mm)		7/8" x 5.6" (22 mm x 142 mm)	
Weight		4.6 oz. (129 grams)		4.2 oz. (119 grams)	
Memory		40,000 readings in FRAM memory, or up to 120,000 readings using data compression option		40,000 readings in FRAM memory, no data compression option	
Communication Speed		9600 bps, 38,400 bps with HS USB Optical Reader		9600 bps	
Com Interface		Optical infra-red: USB, RS232, SDI-12		Optical infra-red: USB, RS232, SDI-12	
Memory Modes		Continuous or Slate		Slate	
Logging Rates		0.125 sec to 99 hours		0.5 sec to 99 hours	
Logging Modes		Linear, Event & User-Selectable Schedules with Repeat Mode, Future Start, Future Stop, Real Time View		Linear, Real Time View, Future Start	
Barometric Compensation		Data Wizard and Barologger Edge		Data Wizard and Barologger Edge	
Corrosion Resistance		Titanium based PVD coating and Hastelloy Sensor		316 L Stainless Steel and Hastelloy Sensor	
Other Wetted Materials		Delrin, Viton, Hastelloy, 316L Stainless Steel		Delrin, Viton, Hastelloy, 316L Stainless Steel	
Direct Read Capability		Yes		Yes	

Apple, the Apple logo, and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Solinst Canada Ltd. is under license.